

ARC AQUA-BLOCK

ONE-COAT INSTANT WATERPROOFING



- ✓ For roofs, gutters, flashing etc.
- ✓ Can be applied in wet conditions
- ✓ Fibre reinforced to bridge gaps & cracks
- ✓ Fully flexible, non cracking
- ✓ Available in Black, Grey & White

Arc Building Products
Gorey Business Park, Gorey, Co. Wexford, Ireland
www.mouldx.com www.arcbuildingproducts.ie www.ms-11.com

☎ +353 (0)53 948 3788 Fax: +353 (0)53 948 3796 ✉ sales@arcbuildingproducts.ie

ARC AQUA-BLOCK

ONE-COAT INSTANT WATERPROOFING

Description

Arc Aqua-Block is a liquid acrylic resin dispersed in solvent and reinforced with fibres to allow the bridging of small gaps and cracks giving instant waterproofing. For external use only.

Advantages

Excellent adhesion – Instant protection – No wash off – White & grey offer excellent solar reflectivity – Reinforced membrane – One coat application – Seamless – Fully flexible – Unaffected by low temperatures to -10°C

Uses

For waterproofing flat and pitched roofs, roof lights, flashing, corrugated asbestos, roofing felt, gutters, slate, asphalt, lead, glasshouses, metal, fibreglass etc.

Application Guide

Clean all moss, lichen, debris and contaminants from the surface. Ensure all corners are clean and gutters are free from plant growth. Aqua-Block can be applied to damp surfaces or when rain is expected but ideally areas should be free of standing water which may contain debris and contaminants. Large cracks, splits and nail holes should be repaired prior to application.

Aqua-Block requires no primer on most surfaces with the exception of asphalt and bitumen which should be primed before application of Arc Aqua-Block. Drying time can be up to 72 hours depending on surface and temperatures. The product may remain soft for a further period but this does not affect it's waterproofing qualities.

Limitations

Inspect surface and carry out an adhesion test to any existing coating or substrate prior to application. Not for use in areas where solvent or oil contact is likely. Not suitable for walkways, balconies, timber and new concrete. Information given is for general guidance only. Refer to product data and safety data sheets for full instructions and precautions in use. Arc cannot accept liability for loss or damage caused by the incorrect use of its products or poor workmanship. The user must ensure the product's suitability for the application intended and if in doubt should seek a written technical specification for the product's application.

Coverage

1-2kg per square metre

Shelf Life

12 months in sealed container.

Store indoors between 5 and 20°C away from sources of ignition.



Gorey Business Park, Gorey, Co. Wexford, Ireland @ www.arcbuildingproducts.ie

+353 (0)53 948 3788 Fax: +353 (0)53 948 3796 ✉ sales@arcbuildingproducts.ie